



INSUL-TEC




DOUBLE HUNG



The secret behind this window's performance is its exceptionally low air infiltration ratings which can lower the energy consumption of a typical home by 25–40%. This unique feature, combined with our HeatSeal® Glass System or HeatSeal® Super Glass System, offers outstanding thermal performance and exceeds the most rigorous Energy Star Requirements.

PowerLift™ allows smooth window operation.

(Block-and-Tackle) balance system used in our windows can achieve life cycles as high as 28,000 cycles. Constant Force commonly used by other window manufacturers only achieves 5,000 cycles.*



* Based on test performed by BSI Hardware-Amesbury Group

- **Stylish Full 3¼" Depth Welded Mainframe** with beveled colonial exterior curves that are not only beautiful, but also allow for maximum weld surface resulting in outstanding strength and years of long lasting performance (1).

- **The Sill Dam Wall** is mortised into the jamb adding strength and lowering the possibility of leaks that may occur at corner seals (2).

- **Fully Integrated Lift Rail** gives this window a nice, contemporary look (3).

- **Standard Slim Profile Sash Lock** with tamper-proof cam ensures a much smoother turn and increases the life cycle over traditional locks (4).

- **Push Button Spring-Loaded Vent Latches** allow both window sashes to remain partially open for ventilation (5).

- **Optional Foam Filled Insulated Extrusions** for energy efficiency.

- **Insulated Extra-Strength Glass** increases strength and sound reduction.

- **Full Interlock with Triple Weather-Stripping** provides low air infiltration for increased comfort.

- **One Piece Sloped Sill** helps eliminate clogged and frozen weep holes as well as reducing air infiltration and chimney effect drafts.

- **HeatSeal Warm Edge Spacer System** for excellent thermal efficiency and drastic reduction in the possibility of condensation on the inside of the window.


- Available in Replacement and New Construction applications.





SLIDER



Smooth Glide System (Standard)



High quality brass wheels allow the slider to smoothly glide across its track.



This system contains an anodized aluminum track and precision ball bearing wheels for smoother glide and operation especially with oversized and triple pane units.



- **Full 3¼" Depth Welded Mainframe** with beveled colonial exterior features curves that are not only beautiful, but also allow for maximum weld surface resulting in exceptional strength and years of long lasting performance.

- **Full Integral Interlock** with double weather-stripping.

- **The Optional Auto-Lock** features an exclusive automatic locking system which is easy to engage.

- **Heavy Gauge Fully Extruded Handles** on both sashes.

- **HeatSeal® Glass System** offers thermal efficiency for fuel cost savings in any season.


- **Fiberglass Mesh Half Screens** standard on all windows.

- **Air Infiltration** for the sliding window is 0.09 cfm/ft²; 222% better than Industry Average. (See Air Infiltration Chart for average)

- Available in Replacement and New Construction applications.

Screen

ThruVision Plus® is our fiberglass improved visibility screen. This product does for windows and doors what high-definition technology has done for television viewing: it improves the view by making it sharper and more vivid.



Industry Average Screen



ThruVison PLUS®
Standard with Insul-Tec Windows

OKNA Windows offers many color selections in addition to the standard Euro-White to give your home a distinct look and enhance its curb appeal. You can special order custom exterior colors from a virtually unlimited selection of paints. Our paints are environmentally safe and durable, giving your exterior a vibrant and long-lasting color finish. **All colors except Euro-White are available at an additional charge.**

Interior Color




Standard Euro-White finish and
Standard Euro-White Lock

Optional Almond frame
and Optional Almond lock

Optional Cocoa frame
and Optional Cocoa lock


Exterior Colors

All colors except Euro-White are available at an additional charge. Printed colors may not match the product's actual color. Please visit a local dealer to view actual color samples.



Air Infiltration


Air Infiltration / drafts is a term used to describe the air leaking into or out of your home through the window frames. The graph shows the amount of air in cubic feet/minute that may come through the window at speeds of 25mph.




US Department of Energy • www.energystar.gov/index.cfm?c=new_homes_features.hm_f_reduced_air_infiltration
The results are based on a tested window sample by AAMA testing window guidelines. Title of Test & Method: Air Infiltration - ASTM E 283 75 PA - (1.6 psf) 25 mph

Grids

Looking for a stunning design to instantly set your home apart both inside and out? A choice of decorative grids can highlight the architectural style that speaks to you. GBG (Grids Between Glass) consist of aluminum bars sealed in the insulating airspace between the two panes of glass. Because the interior and exterior glass surfaces are not affected, cleaning your windows is a much easier task. GBG grids on two tone windows are available with matching interior and exterior colors. Custom colors are not available on GBG grids.



Flat Grids
Between Glass



Contour Grids
Between Glass

Glass

OKNA Windows offers textured glass in a variety of distinctive choices that add visual interest to any design while offering variability in light control. With a range of options at your fingertips, you can find a standard glass texture for virtually every application and aesthetic, from traditional to modern.




Regular Obscure



Niagara

HEATSEAL® GLASS SYSTEM

High Performance
Reflective Coatings Glass



HeatSeal™ heat reflective coatings are microscopically thin layers of metal & metal oxide that act like a filter – some energy is transmitted, some energy is reflected.

High Performance
Glass Unit Spacer

Most windows are manufactured with a metal spacer in between the glass which causes excessive condensation and heat loss.




Our HeatSeal® non-metal spacer creates an excellent thermal barrier and reduces the transfer of heat and cold into the home.

Spacers

Our HeatSeal® Spacer gives your home excellent thermal efficiency and drastic reduction of condensation.

As much as 15.3° F warmer seal temperature at sightline.



Super Spacer® is a registered trademark of Edgetech I.G., Inc./ • Intercept® is a registered trademark of PPG Industries, Inc.DuraSeal is a registered trademark of TruSeal Technologies, Inc. • Swiggle is a registered trademark of TruSeal Technologies, Inc. Simulation performed by Enermodal engineering, Ltd. using Window 5.2. All air spacers are 0.562" wide 0.033 emittance low-E glass.

Basic

ENERGY SAVING PACKAGE

- Heat Seal® Glass System
Double Pane Glass Unit
- No Foam
- Without grids

U-Value	0.27
SHGC	0.29
VT	0.53
CR	62



DELUXE

ENERGY SAVING PACKAGE

- Heat Seal® Glass System
Double Pane Glass Unit
- Foam Filled Extrusions
- Locking Screen
- Without grids

U-Value	0.25
SHGC	0.29
VT	0.53
CR	62



Super Deluxe

ENERGY SAVING PACKAGE

- HeatSeal® Super Glass System
Triple Pane Glass Unit
- Foam Filled Extrusions
- Locking Screen
- Without grids

U-Value	0.19
SHGC	0.25
VT	0.42
CR	73



Super Deluxe

ENERGY SAVING PACKAGE
with KRYPTON GAS

- Heat Seal® Super Glass System
Triple Pane Glass Unit - KRYPTON Gas
- Foam Filled Extrusions
- Locking Screen
- Without grids

U-Value	0.15
SHGC	0.25
VT	0.42
CR	77



SUNSEAL GLASS is specifically designed for homes in the southern climate.

SUNSEAL Basic

- SunSeal® Glass System
Double Pane Glass Unit
- No Foam
- Without grids

U-Value	0.27
SHGC	0.21
VT	0.42
CR	62



SUNSEAL Deluxe

- SunSeal® Double Pane Glass Unit
- Foam Filled Extrusions
- Locking Screen
- Without grids

U-Value	0.25
SHGC	0.21
VT	0.42
CR	62



Tomorrow's Windows ... Today



THERMAL PERFORMANCE (WITHOUT GRIDS)

	Double Hung U-Value	Slider U-Value	Picture U-Value	Energy Star Minimum <i>Northern Climate Zone</i>
HEATSEAL GLASS PACKAGE				
Energy Saving Package	0.27	0.27	0.27	0.27
Deluxe Package	0.25	0.26	0.25	0.27
HEATSEAL SUPER GLASS PACKAGE				
Energy Saving Package	0.22	0.21	0.20	0.27
Deluxe Package	0.19	0.20	0.18	0.27
Deluxe Package - Krypton Gas	0.15	0.16	0.14	0.27

STRUCTURAL PERFORMANCE

	Double Hung (40x63)	Slider (63x44)	Picture (48x48)	Industry Minimum
DUAL GLAZED				
AAMA Rating	R 50	R 40	R 75	R15
Air Infiltration (cfm/ft2)	0.02	0.09	< 0.01	0.3
Water Penetration (mph)	54	59	66	33
Structural Integrity (mph)	171	153	210	94

U-VALUE result are based on tested window sample without grids by NFRC. U-Value, SHGC, VT, CR values may change slightly for windows made with GBG (Grids Between Glass).

WATER PENETRATION mph - Specifies wind load pressure in mph a window can withstand without leaking, under rain equivalent to 8" per hour.

STRUCTURAL INTEGRITY mph - Wind load in mph the window can withstand before breaking.

All result numbers are based on tested window sample by NFRC and AAMA testing window guidelines. Use for comparison purposes only. Actual values may vary depending on installation, size of the window, and other conditions.

All illustrations, photographs, and specifications in this publication are based on the latest product information available at the time of printing. Some windows shown with optional features. See the actual product for complete accuracy. The manufacturer reserves the right to alter or discontinue any model or specification without notice.



400 Crossings Drive
Bristol, PA 19007
(215) 788-7000
(215) 781-1166 (fax)
www.oknawindows.com

